

Instalar MariaDB no CentOS 7

- Instalar o repositório YUM MariaDB Community

- Baixar script oficial do repositório

```
▪ wget https://downloads.mariadb.com/MariaDB/mariadb_repo_setup
```

- Atribuir permissão de execução ao script

```
▪ chmod +x mariadb_repo_setup
```

- Executar script

```
▪ ./mariadb_repo_setup
```

- Instalar MariaDB e suas dependências

- `yum install MariaDB-server`

- Iniciar serviço do MariaDB Server

- `systemctl start mariadb`

- Verificando se o MariaDB iniciou corretamente, Active: active (running) deve ser exibido

- `systemctl status mariadb`

```
[root@ocs gustavo]# systemctl status mariadb
● mariadb.service - MariaDB 10.9.3 database server
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; disabled; vendor preset: disabled)
   Drop-In: /etc/systemd/system/mariadb.service.d
            └─migrated-from-my.cnf-settings.conf
   Active: active (running) since Thu 2022-11-03 12:41:18 -03; 41s ago
     Docs: man:mariabdb(8)
            https://mariadb.com/kb/en/library/systemd/
   Process: 2442 ExecStartPost=/bin/sh -c systemctl unset-environment _WSREP_START_POSITION (code=exited, status=0/SUCCESS)
   Process: 2413 ExecStartPre=/bin/sh -c [ ! -e /usr/bin/galera_recovery ] && VAR= || VAR=`cd /usr/bin/..; /usr/bin/galera_recovery`; [ $? -eq 0 ] && systemctl set-environment _WSREP_START_POSITION=$VAR || exit 1 (code=exited, status=0/SUCCESS)
   Process: 2411 ExecStartPre=/bin/sh -c systemctl unset-environment _WSREP_START_POSITION (code=exited, status=0/SUCCESS)
   Main PID: 2425 (mariabdb)
    Status: "Taking your SQL requests now..."
   CGroup: /system.slice/mariadb.service
           └─2425 /usr/sbin/mariabdb
```

- Habilitando o início automático do MariaDB

- `systemctl enable mariadb`



- Execute o guia de configurações básicas do MariaDB

- `mariadb-secure-installation`

1. Senha do usuário ROOT do MariaDB

1. deixa em branco (Seria necessário caso a senha de root já tivesse sido configurada anteriormente)
2. Switch to unix_socket authentication
 1. n
3. Change the root password? [Y/n]
 1. y
 2. deve usar uma senha forte
4. Remove anonymous users? [Y/n]
 1. y
5. Disallow root login remotely? [Y/n]
 1. y
6. Remove test database and access to it? [Y/n]
 1. y
7. Reload privilege tables now? [Y/n]
 1. y

From:

<https://gugainfo.com.br/> - **GugaInfo**

Permanent link:

<https://gugainfo.com.br/doku.php?id=linux:centos:mariadb>

Last update: **2022/11/03 12:51**

